

Tommy Nielsen



# ROLLER CUTTER



ROLLER CUTTER

# Roller Cutter RS

Tommy Nielsen



The **Roller Cutter RS** are used when perforation in blister packaging is required, allowing tearing off of individual blisters. This perforation is made on a sealed package by a Roller Cutter.



The **Roller Cutter RS** can also be used to cut several formed packages on the same board into single packages and for cutting out of hanging holes (Euro slot). A combination of both at the same time can also be done.

The blisters are placed in a die cutter. This die is pressed through between 2 steel rolls which enables cutting/perforating of the blister packs.


We offer two different sizes of **Roller Cutter** – the RS 420 and RS 650 with a maximum width of 420 mm and 650 mm.

Besides the different size, the difference is that the **Roller Cutter RS 420** has traction only on the bottom roll, whereas the **Roller Cutter RS 650** has traction on both rolls.

Agent:



	Roller Cutter RS 420	Roller Cutter RS 650
A	1232 mm	1200 mm
B	845 mm	900 mm
C	1260 mm	1650 mm
D	725 mm	840 mm
E	539 mm	740 mm
F	430 mm	650 mm



## Roller Cutter RS technical data:

	Roller Cutter RS 420	Roller Cutter RS 650
Function:	Cutting of blisters	Cutting of blisters
Roll width:	420 mm	650 mm
Max. blister depth:	120 mm	120 mm
El. fusing:	16 Amp	16 Amp
El-supply (V):	3 x 400 + PE	3 x 400 + PE
Weight:	190 kg	260 kg

We reserve the right to alter specifications without prior notice.

Tommy Nielsen

Malervej 6 • DK-6710 Esbjerg V • Denmark  
 Phone: +45 75 15 32 00  
 Fax: +45 75 15 02 35  
 E-mail: tn@tommy-nielsen.dk  
 www.tommy-nielsen.dk